

Ultrasonic Cleaner

Multipurpose, top quality cleaners. Customization available.



Multiple Uses

- Cleaning of Glass ware
- Diesel engine / Machinery parts
- Metal parts and tools of Brass, Stainless Steel, Aluminium, Gold, Silver etc.
- Infection Control of surgical equipments, Degassing, Dissolution, Degreasing, Dispersion, Suspension, Sonochemistry, Nanotechnology, etc.



Capacity available : Standard models / as per user needs.

Product Specifications

	FS-6	FS-10	FS-20	FS-45	FS-50	FS-100	FS-120
Operating Capacity	6 Liters	10 Liters	20 Liters	45 Liters	50 Liters	100 Liters	120 Liters
Tank Dim. (mm)	300 x 140 x 150	300 x 240 x 150	500 x 300 x 150	500 x 300 x 200	550 x 425 x 225	600 x 500 x 350	600 x 500 x 400
Operating Voltage	230 VAC, 50 /60Hz	230 VAC, 50 /60Hz	230 VAC, 50 /60Hz	230 VAC, 50 /60Hz	230 VAC, 50 /60Hz	230 VAC, 50 /60Hz	230 VAC, 50 /60Hz
Power O/P.	120 Watts	250/300 Watts	500 Watts	600 Watts	750 Watts	1000 Watts	1250 Watts
Operating Frequency	23 +/- 3 OR 37 +/- 3 Khz.	23 +/- 3 OR 37 +/- 3 Khz.	23 +/- 3 OR 37 +/- 3 Khz.	23 +/- 3 OR 37 +/- 3 Khz.	23 +/- 3 OR 37 +/- 3 Khz.	23 +/- 3 OR 37 +/- 3 Khz.	23 +/- 3 OR 37 +/- 3 Khz.
Tank, Outer body, Basket and Lid Construction	S.S. 304/ SS 316	S.S. 304/ SS 316	S.S. 304/ SS 316	S.S. 304/ SS 316	S.S. 304/ SS 316	S.S. 304/ SS 316	S.S. 304/ SS 316
Timer & Temperature	PLC Control	PLC Control	PLC Control	PLC Control	PLC Control	PLC Control	PLC Control

Optional Items (Capacity and dimensions to suit the Client requirement)

Outer body SS 304. Timer and Temperature with PLC Control



Filtek (India) Pvt. Ltd.

S. No. 34/2/1, Oxford Road, Bavdhan (Bk),

Pune 411021. INDIA

info@filtekindia.com | www.filtekfiltration.in

